

ELECTRONIC CARD CONNECTOR

BACKGROUND OF THE INVENTION

1. The field of the invention

[0001] The present invention generally relates to an electronic card connector, and
5 more particularly to an electronic card connector comprising an upper lid that can be opened or closed by rotating the upper lid along an axis at one end or sliding the upper lid.

2. Description of the related art

[0002] Nowadays, in a well-developed information technology era, the cellular phone has become one of the most popular and essential communication tools for users.

10 Along with the increased numbers of the cellular phones, there also exist a variety of types and styles of the cellular phones with improved functionalities. From the first generation of the cellular phone to the latest model, the trend of smallness, lightness, flatness, portability and good reception continues. Sometimes, a user may need more than one cellular phone due to different usage conditions, for example, different
15 frequency for different countries. Therefore, the cellular phones are designed in various models and styles to meet the users' requirement. When the user needs to switch the cellular phone into another cellular with the same number, the user has to remove the **SIM** electronic card from the phone and fit into the electronic card connector of the other cellular phone.

20 [0003] Referring to FIG. 6, a side view of a conventional electronic card connector is shown, wherein the electronic card connector comprises a base **A** and an upper lid **B**. The base **A** comprises an axle **A1** at the two distal ends, and at the two sides of the base **A** have a plurality of protrusions **A2**. The protrusion **A2** has buckling groove **A21** at a

bottom thereof. Bent suspended arms **B1** extend downwardly at the two sides of the upper lid **B** and passing around the axles **A1**. The bent suspended arms **B1** are capable of rotating along the axels **A1** for opening or closing the upper lid **B**. On the two sides of the upper lid **B** comprise buckling plates **B2** corresponding to the buckling grooves **A21**.

5 However, there is no fixed positioning arrangement for the bent suspended arms **B1** to rotate along the axles **A1**, thus the upper lid **B** may rotate or move along any position of the bent suspended arms **B1** misaligning the buckling plate **B2** of the upper lid **B** and fall on the top face of the protrusion **A2** of the base **A**, in such occasion, any external force applied on the upper lid **B** can easily cause deformation of the shape of the buckling plate
10 **B2**.

[0004] Because the conventional design can easily misalign the buckling plate **B2** of the upper lid **B** making it difficult to fit into the buckling groove **A21** formed on the side of the protrusion **A2** of the base **A** for positioning. Further, a long-term usage under this condition, the buckling plate **B2** will be deformed or damaged and thereby damaging
15 the upper lid **B**. Therefore, to find a way to improve the above defects is a very important issue for the manufacturer in the field.

SUMMARY OF THE INVENTION

[0005] Accordingly, in the view of the foregoing, the present inventor makes a detailed study of related art to evaluate and consider, and uses years of accumulated
20 experience in this field, and through several experiments, to create a new electronic card connector. The present invention provides an innovated, cost effective electronic card connector.

[0006] According to an aspect of the present invention, the electronic card connector comprises a protrusion formed on the suspended arm to rotate corresponding to the base, thus the upper lid is able to rotate in a fine range to prevent damages to the electronic card connector from occurring.

5 **BRIEF DESCRIPTION OF THE DRAWING**

[0007] For a more complete understanding of the present invention, reference will now be made to the following detailed description of preferred embodiments taken in conjunction with the accompanying drawings.

[0008] Fig. 1 is the elevational view of an electronic card connector of the present
10 invention.

[0009] Fig. 2 is a top view of the electronic card connector of the present invention.

[0010] Fig. 3 is a side view of the electronic card connector of the present invention with the upper lid opened.

[0011] Fig. 4 is a side view of the electronic card connector of the present
15 invention while the upper lid is closing.

[0012] Fig. 5 is a side view of the electronic card connector of the present invention with the upper lid closed.

[0013] Fig. 6 is a side view of a conventional electronic card connector.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

20 [0014] Reference will be made in detail to the preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts.

[0015] Referring to FIG. 1, the elevational view of the electronic card connector of the present invention is shown. The electronic card connector comprises a base 1 and an upper lid 2. The base 1 comprises a plurality of conductive terminals 10 for transmitting/retrieving signals for reading/retrieving data. The base 1 comprises two
5 axles 11 positioned on two distal ends of two sides thereof. A plurality of protruded blocks 12 having buckling grooves 121 are positioned along two sides of the base 1 as shown in FIG. 1. The upper lid 2 comprises suspended arms 21 formed on the distal ends of two sides thereof, wherein the suspended arms 21 are bent into a U shape with the open end facing towards frontal part of the electronic card connector. The suspended
10 arms 21 are positioned around the axles 11 capable of rotating along the axles 11 as an axis. The suspended arms 21 comprises buckling plates 22 on two sides thereof, wherein the buckling plates 22 are positioned corresponding to the buckling groove 121. The suspended arms 21 formed on the two sides of the upper lid 2 comprise a protrusion
211 formed on a surface thereof. An indentation 13 is formed on the base 1 such that the
15 indentation 13 is positioned corresponding to the suspended arm 21. A track 111 is formed at a bottom part of the axle 11 that correspond to the protrusion 211.

[0016] Referring to FIG. 3, 4 and 5, respectively show the side view of the electronic card connector of the present invention with the upper lid opened, the side view of the electronic card connector of the present invention while the upper lid is
20 closing, and the side view of the electronic card connector of the present invention with the upper lid closed. When the upper lid 2 opens, the position of the protrusion 211 allows the upper lid 2 to rotate along the axle 11 of the base 1, and as the upper lid 2 reaches a certain position during the closing action, the protrusion 211 will have a

freedom to move along a horizontal direction along the track **111**, and therefore the buckling plates **22** of the upper lid **2** can buckle into the buckling groove **121** of the protruded blocks **12** formed on the two sides of the base **1** for proper positioning. The design of the track **111** is to secure the upper lid **2**. When the upper lid **2** is secured, the protrusion **211** is supported on the lower portion of the track **111** to prevent the upper lid **2** from opening in an inappropriate position so that damages of due to any external force can be effectively prevented.

[0017] The suspended arms **21** is designed with a inclined angle in a manner to increase the internal strength of the suspended arm **21** for allowing the protrusion **211** to be steadily supported at the axle **11**. Accordingly, even after a long-term usage of the suspended arm **21** of the upper lid **2**, the positioning of the upper lid **2** with respect to the axels **11** will remain steady. Besides, the indentation **13** is formed in the base **1** corresponding to the suspended arm **21** will allow the upper lid **2** to close more smoothly, and the suspended arms **21** will hold on to the side with the inner portion to prevent the upper lid **2** from shaking.

[0018] In the preferred embodiment of the present invention, the axle **11** of the base **1** comprises the track **111** to allow the protrusion **211** of the suspended arm **21** to move in an appropriate position, and the position or shape of the track **111** can be designed according to the practical need, and the figures thereof is only for the purpose of demonstrating the preferred embodiment and not to restrict the scope of the present invention.

[0019] According to an aspect of the present invention, the strength of the buckling plate **22** of the upper lid **2** is smaller than the protruded blocks **12** of the base **1**, so that the buckle plate **22** of the upper lid **2** may have certain degree of transfiguring.

[0020] While the invention has been described in conjunction with a specific best
5 mode, it is to be understood that many alternatives, modifications, and variations will be apparent to those skilled in the art in light of the foregoing description. Accordingly, it is intended to embrace all such alternatives, modifications, and variations in which fall within the spirit and scope of the included claims. All matters set forth herein or shown in the accompanying drawings are to be interpreted in an illustrative and non-limiting sense.